



Hydraulic Filter Carts

Keep your system clean and extend the life of your hydraulic system every time you transfer fluid

Standard Models

Model HHFC5—5 Gallons Per Minute Flow Rate

Model HHFC10—10 Gallons Per Minute Flow Rate

Model HHFC15—15 Gallons Per Minute Flow Rate

Inquire for custom models

Standard Features

110 Volt AC Single Phase Motor

2 high volume filter heads to provide max cleaning and different filter choices

Replacement filters are inexpensive and easy to change

Color coded filter life indicator gauges for each filter

6 foot hoses on the inlet and outlet sides with 3 foot wands to reach bottom of 55 gallon drums

On / Off Toggle Switch

10' cord with 110V molded plug

Y-strainer filter for pump protection

Rugged cart with solid tires

All tubing stainless steel

Optional: Virtually any flow rate available.

Inquiries

Contact: Sales Department

Tel: 713-692-4421

Sales@HouHyd.com

Why Use a Filter Cart?

Time is money: Empty a 55 gallon drum in less than 4 minutes with our standard 15 gpm filter cart.

Stay on budget: Filtering fluid every time you transfer it ensures longer equipment and fluid life. This means less unscheduled downtime and lower unexpected maintenance costs.

Ease of use: Clear hoses & indicator gauges provide visual indication of transfer status and filter life.